

Maintenance of Tech-Wood® Decking

Tech-Wood® Decking does not need any maintenance to guarantee its durability.

Tech-Wood® Decking will become grey in due time. This greying process can be compared with traditional wood like Balau (Bangkirai). The weathering of the upper surface of Tech-Wood® Decking is caused by the natural process of oxidation of the wood fibres, present in the product. Each of the 6 colours will develop its own greying tone, from silver-grey to brown- / black-grey. The ultimate greying is influenced by surrounding factors like shadow, air pollution, the season and maintenance. The pictures and samples provided by Tech-Wood® give an indication of the weathering and are therefore not always representative.

Tech-Wood® Decking is a product which is poor in maintenance. Its natural durability makes any protective treatment redundant and it is therefore very well suitable for applications like patios, balconies, galleries, bridges (pedestrian), roof-terraces, marinas and swimming pools.

If mounted correctly and the maximum load is not being exceeded, you can confine yourself with cleaning Tech-Wood® Decking now and then.

Cleaning of Tech-Wood Decking®

Tech-Wood® Decking can easily be cleaned. Moss, algae and other dirt can be removed with hand-warm water and a brush or with a high pressure cleaner. Soap-like products can be added to the water, without harming the product. Under no circumstances organic or chemical solvents, acids or lixivium should be used.

Heavy pollution like grease or oil is to be removed immediately. A treatment with a cleaning sponge or a steel brush is often necessary to remove the stains. The 'fresh' surface that is being created by this treatment will become grey again in due time.

Cigarette stains of chewing gum can also be removed with a cleaning sponge or a steel brush, followed by a treatment with water.