

Maintenance of Tech-Wood® Siding

Tech-Wood® Siding does not need any maintenance to guarantee its durability. Because of its unique composition, Tech-Wood® does not need any lacquer to prevent the product from decaying. None-lacquered Tech-Wood® Siding will become grey in due time. This unique greying, which resembles the greying of traditional wood, is influenced by surrounding factors like shadow, air pollution, the season and maintenance.

For aesthetic reasons, we advice to inspect, clean and (if desired) treat lacquered Tech-Wood® Siding now and then. For a facade with lasting beauty we advice* to:

Advice in maintenance for Drywood lacquered finish

Treatment	in 1st year	In 2nd year	In 3rd year	In 4th year	In 5th year	In 6th year	In 7th year	In 8th year	In 9th year	In 10th year
Inspection for mechanical damages and if necessary retouch the surface	*	*	*	*	*	*	*	*	*	*
Cleaning of the surface with a brush and afterwards scouring with paint cleanser. Re-paint the surface once with a lacquer in a dry layer of 40 - 50 micron thickness.							*			

Advice in maintenance for Drywood stain finish(wood colours)

Treatment	in 1st year	In 2nd year	In 3rd year	In 4th year	In 5th year	In 6th year	In 7th year	In 8th year	In 9th year	In 10th year
Inspection for mechanical damages and if necessary retouch the surface	*	*	*	*	*	*	*	*	*	*
Cleaning of the surface with a brush and afterwards scouring with paint cleanser. Re-paint the surface once with a stain or lacquer in a dry layer of 40 - 50 micron thickness.			*			*			*	

*Tech-Wood Nederland BV guarantees the durability of its products for a period of 10 years, in accordance with her general terms of delivery.
For lacquered Tech-Wood® Siding a supplementary guarantee of 10 years is given for the coating.
For this, supplementary terms apply, which are mentioned on the backside.

Guarantee of Tech-Wood® Siding

In addition to her standard product guarantee according to her general terms of delivery, Tech-Wood Nederland BV guarantees the coating applied onto Tech-Wood® Siding against material damage which is caused by application failures for a period of 10 years.

With material damage is meant:

- detachment class 2 or higher in accordance with ISO 2409 : 1992
- Peel off class 2 or higher in accordance with ISO 4628/5 : 1982
- Blistering class 2 or higher in accordance with ISO 4628/2 : 1982

Excluded of this guarantee is the pulverization and fading of the coating by UV-sunlight without due regard to the maintenance interval of the maintenance advice of Drywood Coatings B.V.